




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H01S 3/16, A61B 17/36, H01S 3/092, 3/102		A1	(11) International Publication Number: WO 96/33538
			(43) International Publication Date: 24 October 1996 (24.10.96)
(21) International Application Number: PCT/US96/04515		(81) Designated States: JP, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 2 April 1996 (02.04.96)		Published With international search report. With amended claims and statement.	
(30) Priority Data: 08/422,827 17 April 1995 (17.04.95) US			
(71) Applicant (for all designated States except US): COHERENT, INC. [US/US]; 5100 Patrick Henry Drive, Santa Clara, CA 95056 (US).			
(72) Inventors; and (75) Inventors/Applicants (for US only): MITCHELL, Gerald, M. [US/US]; 1687 Dalehurst Avenue, Los Altos, CA 94024 (US). REED, Edward, D. [US/US]; 1667 Lewiston Drive, Sunnyvale, CA 94087 (US). SPOONER, Greg, J. [US/US]; 223 Ramona Street, Palo Alto, CA 94301 (US). HMELAR, Michael [US/US]; 3144 Maddux Drive, Palo Alto, CA 94303 (US).			
(74) Agents: STALLMAN, Michael, A. et al.; Limbach & Limbach L.L.P., 2001 Ferry Building, San Francisco, CA 94111 (US).			

(54) Title: HIGH REPETITION RATE ERBIUM: YAG LASER FOR TISSUE ABLATION

(57) Abstract

A medical laser system (10) is disclosed for ablating biological material. The system includes an Erbium: YAG gain medium (24) capable of generating a pulsed output having a wavelength of 2.9 microns. The laser is optimized to generate a pulsed output having a repetition rate of at least 50 hertz and preferably at least 100 hertz. The output is delivered to the target tissue via an optical fiber (82). Preferably, a suction source is provided to aspirate the tissue as it is being ablated. The erbium laser system provides accurate ablation with minimal damage to surrounding tissue.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

**HIGH REPETITION RATE
ERBIUM:YAG LASER FOR TISSUE ABLATION**

Technical Field

5 The subject invention relates to a medical laser system for ablating and emulsifying biological material.

Background of the Invention

10 In recent years, there has been a significant amount of progress made in developing solid state laser systems for medical applications. Today, commercial systems are available which generate pulsed outputs at a variety of wavelengths. Many of the early solid state medical laser systems were based on neodymium doped gain media which generate a
15 near infrared output wavelength of 1.06 microns. Using specific frequency selective optics, Nd:YAG medical lasers systems have also been developed which generate an output of 1.44 microns. (See, for example, U.S. Patent No. 5,048,034).

20 It has been known for some time that tissue ablation can be enhanced through the use of infrared wavelengths that more closely match absorption peaks of water, the major constituent in biological tissue. To this end, the assignee herein (as well as others)
25 have introduced medical laser systems which include a gain medium wherein holmium is the lasing species. These laser systems generate an output wavelength of 2.1 microns. The absorption coefficient in water for 2.1 micron radiation is more than two hundred times
30 greater than the absorption coefficient of 1.06 micron radiation. This greater absorption coefficient means that more energy will be absorbed at the surface of the tissue (rather than penetrating into the tissue) resulting in cleaner ablation with
35 less thermal damage.

One problem with the holmium laser systems is that they cannot easily be configured to generate the same output powers associated with Nd:YAG systems. To address this problem, multiple head laser systems have been developed, wherein each system includes two or more laser resonators, each having a holmium:YAG laser rod. The pulsed outputs of these laser resonators are interleaved and combined along a common output path to generate an output having a higher average power and higher repetition rate. Such system is described in U.S. Patent No. 5,374,132, issued December 20, 1994, assigned to the same assignee herein and incorporated by reference. (See also, U.S. Patent No. 5,307,211) While the approach of using multiple resonators has been commercially successful, it is more complex and expensive than using a single resonator.

More recently, the industry has been exploring the use of erbium doped gain media for medical applications. Erbium doped YAG crystals will generate an output wavelength of 2.9 microns which is matched to a prominent absorption peak in water. Radiation at 2.9 microns has an absorption coefficient in water about two hundred times greater than 2.1 micron radiation. While this strong absorption in water would seem to make erbium laser systems the ideal candidate for tissue ablation in medical laser systems, certain problems arose.

One primary problem related to the lack of suitable optical fibers for delivering the 2.9 micron radiation. Common silica based fibers transmit 2.9 micron radiation with very low efficiency. Fluoride based fibers, which attenuate the 2.9 micron radiation to a much lesser extent than silica fibers, are relatively toxic to the human body. More recently, improvements in the fiber delivery

technology have made the use of erbium laser light more viable.

Efforts have also been made to increase the pulse repetition rate of erbium laser systems having a single resonant cavity. Quite recently, a system was introduced which could generate a pulsed output at a maximum rate of 30 Hertz. Unfortunately, attempts to increase the repetition rate even higher result in a significant reduction in output power as well as an increase in the thermal loading of the laser rod leading to instabilities.

Summary of the Invention

The subject invention is based, in part, on the recognition that the extremely high coefficient of absorption of 2.9 micron radiation in water allows tissue to be cleanly ablated, vaporized and/or incised at relatively low energy levels per pulse. Moreover, it has been recognized that ablation efficiency can be dramatically enhanced if a relatively high pulse repetition rate is used, even if the energy per pulse is relatively low. Optimal performance can also be enhanced by utilizing a delivery system which functions to simultaneously aspirate the tissue as it is being ablated or emulsified.

In initial experiments, the speed at which certain tissue ablation and incision procedures were performed was vastly increased using a high repetition rate, low energy per pulse, Er:YAG laser. For example, the subject laser was utilized to perform a photophacoemulsification, a common ophthalmic procedure where the lens in the eye is ablated. This procedure can take a number of minutes using a mechanical device. In contrast, using the subject erbium laser, this procedure was performed in

less than 40 seconds. Other examples will be discussed below.

5 In accordance with the subject invention, a system is provided which includes an erbium doped, solid state gain medium mounted in a resonant cavity. The gain medium is excited by a flashlamp which is energized with a power supply. The power supply is controlled in a manner to generate a pulsed output of at least 50 hertz, and preferably greater than 100
10 hertz. At this repetition rate, high precision, high speed tissue ablation and smooth, fluid incisions can be achieved.

It is believed that the threshold for ablating or incising biological material can be as low as 0.5
15 millijoules per pulse delivered to the tissue. By optimizing the design of the laser system, it is believed that high repetition rates can be achieved while still maintaining reasonable output powers, on the order of 50 to 150 millijoules per pulse at the
20 output coupler. At this level, the energy density needed for tissue ablation and incision can easily be delivered to the treatment site.

In one significant aspect of the subject invention, the reflectivity of the output coupler has
25 been increased with respect to a conventionally optimized system. Increasing the reflectivity of the output coupler reduces the slope efficiency of the laser which would be a concern if the laser were to be operated at high powers. Of more importance,
30 increasing the reflectivity of the output coupler also functions to reduce the threshold input for achieving lasing action. By this arrangement, lower input powers may be used which permits the pulse repetition rate to be increased without causing the
35 laser to become unstable.

Another modification which can be employed to enhance the performance of the laser is to provide concave surfaces on the ends of the gain medium. These concave surfaces function to counteract the focusing effects associated with thermal lensing in the rod. It may also be desirable to include selective filters between the flashlamp and gain medium to reduce exposures to light energy which merely serves to heat the gain medium, rather than contributing to the excited states.

Additional details about the subject invention and its method of use will become apparent from the following detailed description, taken in conjunction with the drawings, in which:

Brief Description of the Drawings:

Figure 1 is a schematic diagram of a medical laser system formed in accordance with the subject invention.

Figure 2 is graph illustrating the variation in threshold pump energy as a function of the percentage output coupling which is used in the laser.

Figure 3 is a graph illustrating the improvements in stability which can be achieved using curved end faces on the solid state gain medium.

Figure 4 is a graph illustrating the use of various optical elements having different transmission characteristics to filter the light reaching the gain medium from the flashlamp.

Figure 5 is a schematic diagram of a laser system having two resonant cavities which can generate higher pulse repetition rates using a time-multiplexed output.

Figure 6 is a graph illustrating the time-multiplexed output which can be used in the laser system of Figure 5.

Figure 7 is a schematic diagram of a laser system having four resonant cavities which can generate still higher pulse repetition rates using a time-multiplexed output.

5 Detailed Description of the Preferred Embodiments

Figure 1 illustrates a laser system 10 formed in accordance with the subject invention. Laser system 10 includes a laser head consisting of a resonant cavity defined by a high reflecting mirror 20 and a partially reflecting output coupler 22. A gain medium 24 is positioned within the resonant cavity. Gain medium is defined by an erbium doped solid state crystal. The most common erbium doped crystal is Er:YAG which generates an output wavelength of 2.9 microns. Another common host crystal is YSGG which when, doped with erbium, will generate an output of 2.8 microns.

The gain medium 24 is excited by a flashlamp 30. The gain medium and flashlamp are preferably mounted in a closely coupled cavity of the type described in U.S Patent No. 5,375,132. This type of cavity can include a jacket formed from BaSO₄ acting as a diffuse reflector and maximizing the efficiency of the flashlamp 30.

25 The flashlamp is energized by a power supply 32. The power supply 32 is connected to a conventional controller 34 which may include a microprocessor with external inputs.

30 In accordance with the subject invention, the controller and power supply are operated in a manner to generate a pulsed laser output at a high repetition rate. In the preferred embodiment, the laser is operated at a minimum of 50 hertz, and preferably at least 100 hertz.

In order to insure stable operation at this high repetition rate, a number of laser parameters must be properly optimized. First, the length of activation of the flashlamp pulses should be on the order of 100 to 200 microseconds. The output pulses from the laser will typically be about thirty percent shorter than the flashlamp pulses. In addition, it would be desirable to reduce the average input power to the gain medium to minimize thermal loading and the associated thermal lens effects.

The principal approach which is used in the subject system to reduce the average input power is to increase the reflectivity of the output coupler. In a typical erbium laser system, an output coupler having ten percent transmission might be selected in order to maximize the slope efficiency, and produce a relatively high output power for a given input power. In the subject laser system, the transmission of the output coupler is reduced to between eight and two percent and in the preferred embodiment, is set at four percent.

Figure 2 is a graph plotting data which was obtained in some early experiments and illustrates the threshold pump energy as a function of the transmission level of the output coupler in an erbium laser. As can be seen in this graph, where the output coupling was set at ten percent transmission, the threshold pump energy was close to 13 joules. However, by reducing the transmission of the output coupler to only four percent, the threshold was also be reduced to under 9 joules. In the preferred design discussed below, the lasing threshold has been reduced to 5 joules input power.

As is well known, reducing the transmission of the output coupler also reduces the efficiency of the laser so that more energy would be needed to generate

high energy output pulses. However, and as noted above, it has been recognized that clean ablation, incision or emulsification can be achieved with relatively low energy pulses (i.e. 100 millijoules or less at the output coupler and as little as 0.25 to 0.5 millijoules delivered to the tissue). By reducing the transmission of the output coupler, it is possible to obtain the desired output pulse energy with significantly lower energy input pulses. Having a lower input energy per pulse, allows the repetition rate to be increased without exceeding the maximum average input power level associated with thermal instability. In the preferred embodiment, the input energy per pulse ranges from five to 20 joules. At an input of five joules, lasing will just be initiated. If the system is properly optimized with the procedures discussed below, a stable output of up to 150 millijoules per pulse at the output coupler can be generated with an input energy to the flashlamp of 20 joules.

To further enhance the stability of the laser and allow operation at higher repetition rates and input powers, it is also desirable to provide correction for the thermal lensing effects in the resonant cavity. In the preferred embodiment, this result is achieved by providing the ends of the gain medium with a concave configuration. The concave configuration, which can be a spherical surface having a 20-30cm radius, provides a pair of lenses with negative focal powers in the cavity which offset the positive thermal lens formed in the gain medium.

Figure 3 illustrates the benefits which can be achieved using radiused end surfaces on the gain medium. Figure 3 illustrates the variation of the radius of the laser beam within the rod as a function

of the strength of the positive thermal lens in the rod. The curves in Figure 3 illustrate the stability regions of the laser. Curve 50 illustrates a rod with flat end surfaces and demonstrates that the center of the stability curve occurs when the thermal loading on the rod creates a thermal lens of 100 diopters per meter in strength. Curve 52 illustrates a rod with radiused ends. As can be seen, providing the rod with radiused ends shifts the stability curve in a manner such that the center of the curve 52 occurs at about 160 diopters per meter of thermal lensing which corresponds to significantly higher thermal loads. A laser having a gain medium with radiused ends can be operated with higher energy input pulses and at a higher repetition rate without becoming unstable.

There are other approaches which can be used to further enhance stability. For example, a bandpass filter 60 can be provided between the flashlamp and the gain medium. The filter can be formed from a material which will transmit radiation which most efficiently excites the erbium lasing transitions and absorbs high energy photons which primarily heat the crystal.

Figure 4 is a graph illustrating the changes in performance which can be achieved using different filters. The graph plots the average output power from the laser as a function of input power. The data was taken for a laser operating at a repetition rate of 150 hertz and an output coupler with a four percent transmission level.

Each of the filters illustrated are "cut-off" filters which transmit most of the light above a certain wavelength and absorb most of the light below that wavelength. The filter identified as "Nonex" is soda lead borosilicate glass from Corning (glass code

7720) that has a cut-off at roughly 400 nanometers. The remainder of the filters are colored glasses (O=orange; Y=yellow) having cut-offs at the wavelengths indicated by the number following the letter code.

5

As can be seen, at low powers, the Nonex filter is highly efficient, permitting the generation of the most output power for a given input power. However, at higher input powers, a laser using the Nonex filter became unstable.

10

As can be appreciated, the selection of a particular filter will be based upon the desired operating parameters. In general, the filter selected will permit high output powers to be generated without the laser becoming unstable due to thermal lensing, while at the same time, minimizing the input power necessary to achieve a given output power. In the graph of Figure 4, the filters identified as O-580 and Y-500 are good choices to maximize output power while minimizing thermal lensing effects for the tested laser operating at 150 hertz.

15

20

It should be pointed out that the various specific, individual concepts discussed above for optimizing the subject erbium laser system are not, in and of themselves new. For example, it is known that providing radiused ends on a gain medium can help to compensate for thermal lens effects. Similarly, it is known that filtering a flashlamp can increase the efficiency of a laser system. (See U.S. Patent No. 5,243,615 issued September 7, 1993 to Ortiz). However, it is believed these approaches have not been combined and utilized to provide a substantial increase in the repetition rate of an erbium laser system in a manner to provide

25

30

35

significantly more effective and high speed ablation of biological material.

5 In the most current prototype of the subject invention, the laser includes an Er:YAG rod 4mm in diameter and 90mm in length and the ends of the rod are provided with concave, radiused ends having a curvature of 30cm. The resonator mirrors have a slight radius (one meter curvature) but could be planar. The resonator is symmetric with the mirrors
10 being equally spaced from the ends of the rod by 11cm for a total resonator length of 31cm. A Xenon flashlamp was used and operated at 100, 150 and 200 hertz repetition rate.

15 In addition to maximizing the repetition rate generated by a single laser head, further enhancements can be achieved using multiple laser heads and time multiplexing the output pulses. There are many examples of such approaches in the prior art including the designs set forth in U.S. Patent Nos.
20 5,374,132, and 5,307,211 cite above. This type of system is generically illustrated in Figures 5 and 6.

In these type of systems, the output of two or more lasers 70 and 72 are combined along a common output path using some form of optical combiner. In
25 Figure 5, a tilting mirror or galvanometer 74 is shown. The controller to the power supplies of the lasers 70 and 72 is configured so that both lasers will generate an alternating, pulsed output. For example, and as schematically illustrated in Figure
30 6, both lasers can be configured to generate a pulsed output at 100 hertz. However, the timing of the pulses is arranged so that when one laser is generating a pulse, the other laser is not. The moving mirror 74 can be used to interleave the pulses
35 to generate an output train at 200 hertz.

Mirror 74 is arranged to tip back and forth between two positions. In a first position (shown in solid line of Figure 5), the mirror reflects the output beam from laser 70 along the common output path. After the output pulse from laser 70 is finished, mirror 74 will move to the second position (shown in phantom line) where it can reflect the output pulse from laser 72 along the common output path. The mirror will continue to move back and forth between the two positions to generate the desired output stream.

Figure 7 illustrates how the concept of combining multiple outputs could be expanded to four laser resonators. As shown therein, the output from a first pair of laser resonators (80 and 82) can be combined by a galvanometer mirror 84 along a first, intermediate output path 86 in the same manner as shown in Figure 5. Similarly, the output from a second pair of laser resonators (88 and 90) can be combined by a second galvanometer mirror 92 along a second, intermediate output path 94. The outputs directed along the two intermediate paths can then be combined by third galvanometer mirror 96 along a main common output path 98. Using this approach, the repetition rate of the final output train will be four times higher than the repetition rate for each of the individual laser resonators.

Various other optical beam combiners can be used to multiplex the output of a plurality of pulsed lasers. For example, U.S. Patent No. 5,307,211 describes the use of a spinning disc having reflective and transmissive quadrants. U.S. Patent Nos. 5,374,132 describes the use of a spinning angled reflector.

Since the use of multiple laser heads and time-multiplexing can add costs and complexity to the

system, it is believed preferable to initially maximize the pulse repetition rate that can be obtained from a single laser head. If still higher pulse repetition rates are desirable, then the pulsed output of multiple heads which have been individually optimized can be combined in the manner described above.

As described above, the intent of the subject invention is to provide a laser system particularly suited for ablation, precise, continuous incisions, vaporization and/or emulsification of biological material. To further facilitate this goal, it has been found desirable to combine the lasing action with aspiration at the treatment site. One type of mechanism for achieving this result is illustrated in Figure 1.

As shown therein, the light output from the erbium laser is coupled out of the housing 80 into an optical guide 82 which can be defined by an optical fiber. One type of fiber which is suitable for carrying erbium laser light with reduced attenuation includes germanium oxide Type IV fiber. Such a fiber is described in U.S. Patent No. 5,274,728 issued December 28, 1993 to Tran and is manufactured by IFS Systems. Sapphire fibers can also be used to transmit erbium radiation. Sapphire fibers are available from Saphikon.

It would also be possible to deliver the light through hollow waveguides. Such waveguides often include multi-layer dielectric coatings to enhance transmission. It may also be desirable to deliver the erbium laser light through an articulated arm of the type typically used to deliver the treatment beam in a carbon dioxide medical laser system. An articulated arm delivery system will be necessary if the power of the treatment beam is greater than the

power density handling characteristics of the optical fibers.

5 The distal end of guide 82 feeds into a probe 84 which is designed to be placed next to the region of biological tissue to be ablated. At the present time, there exist a large number of different types of delivery probes, many of which are specifically designed for specific medical procedures. Figure 1 is intended to illustrate a generic probe. As can be
10 seen, the guide 82 is mounted within the probe. A channel 84 is also provided within the probe and communicates with a vacuum source through fitting 88.

 During use, the vacuum source can be employed to aspirate material which has been fragmented or
15 emulsified by the pulsed erbium laser light. The vacuum source can also be used to draw the tissue into close proximity with the delivery end of the guide thereby facilitating its destruction.

 It is believed that the subject, high repetition
20 rate, high precision erbium laser system, which generates an output wavelength which is highly absorbed in tissue, can be used in a number of procedures to improve the ablation, incision, vaporization and emulsification of biological tissue.
25 Some preliminary experiments have already been performed with a prototype system to confirm these beliefs.

 One of the principal fields which can benefit from the use of the subject system will relate to
30 ophthalmic applications. For example, one common ophthalmic procedure requires the removal of a lens having cataracts. The common approach for performing this removal is to use an ultrasonic device which is inserted into the eye for breaking the lens into
35 small pieces. The small pieces are then aspirated. This procedure will typically take several minutes to

perform. This procedure must be done very carefully to insure that endothelium of the eye is not compromised.

5 In accordance with the subject invention, a lens can be emulsified using the pulsed output from the erbium laser. As noted above, the ablation threshold of tissue is quite low, so only relatively low powers are necessary. In an initial experiment using an erbium laser operating at 100 hertz, a cadaver lens
10 was completely emulsified and aspirated in only 37 seconds. Even faster emulsification rates were achieved using a laser system operating at 200 hertz.

Another advantage to the high repetition rate erbium laser is that the temperature rise in the
15 tissue is much lower than would be encountered in an ultrasonic procedure such that the potential for damage of the epithelium is minimized. In this regard, it should be noted that the high absorption and short penetration depth of 2.9 micron light in
20 tissue means that the destructive radiation can be accurately targeted and heating will not spread beyond the treatment region. These attributes make the high repetition rate erbium laser extremely attractive for use with fragile tissue typically
25 encountered in the eye.

Another ophthalmic procedure which would be a good candidate for the subject high repetition rate erbium laser would be photovitrectomy. In this procedure, the vitreous in the eye must be removed.
30 This procedure is presently performed using a mechanical chopper. In initial experiments with the high repetition rate erbium laser, the vitreous can be emulsified and removed at least ten times faster than with a mechanical system.

35 One particular benefit to this approach is that the aspirating channel 84 can be made much smaller

than would be necessary in a mechanical procedure. In a mechanical procedure, the vitreous is chopped into pieces which must fit within the channel. In contrast, with an erbium laser, the vitreous is
5 emulsified or liquified and can be sucked into a small bore. The benefit of a small bore is that it will prevent unwanted material from being sucked into the probe. In addition, in a mechanical procedure, strands of vitreous are sometimes sucked into the
10 probe. These strands are attached to the eye and can tug on fragile tissue such as the retina, causing severe damage. In contrast, the erbium laser immediately emulsifies the ends of the strands so that strands will not be tugged towards the probe by
15 the suction force.

Other ophthalmic procedures which may benefit from the subject high repetition rate erbium laser include capsulotomies, sclerostomies, excision of pupillary membranes, cutting of vitreous bands and
20 iris margin and strand trim work. The high precision of this system could be used effectively in refractive surgery, creating drains when treating chronic glaucoma, clearing tear ducts and scleral cyst removal.

25 It is believed that high repetition rate erbium systems will be beneficial in medical applications which have previously been performed with lower repetition rate systems. For example, there has been significant experimental work performed investigating
30 the application of erbium laser light in dental applications. The applications include drilling teeth, removal of carries, etc. The erbium laser will also be useful for shaping and or removing bones and connective tissue such as cartilage, ligaments
35 and tendons. The erbium laser system can also be used to open passages that pinch nerves, remove

pathologic matter caused by Osteoarthritis and for spine disk modification (percutaneous discectomy).

5 Since the erbium wavelength generates only minimal thermal damage beyond the treatment region, it should also be useful in procedures which need an extremely high degree of position accuracy. One such application will include the shaving of material adjacent to the nervous system as well as brain tissue removal and treating brain abscesses.

10 Similarly, the erbium system could be used for inner ear operations including stapedectomies and maxillary sinus osteotomies.

The erbium laser system could also be used for targeted removal of cancerous tissue and/or tumors in the gall bladder, larynx, liver, glands, pancreas, lungs, stomach, thyroid and trachea. The system could also be used for organ removal such as in a hysterectomy and in gall bladder removal. The laser could also be used to remove fatty tissue (liposuction).

15

20

The erbium laser system can be used in a variety or urinary organ procedures such as kidney wall modification, stone (calculi) fragmentation and removal in the kidney, gall bladder and ureter (lithotripsy), transurethral incision of the prostate, prostatectomy, ureter lesion removal, vasal tissue removal, nephrectomy, vasovasotomy and lymph node modification. In the vascular system, the high repetition rate, precision erbium laser system could be used to open strictures in the aorta, modify vessels at an aneurysm, for clearing vessels (angioplasty) and clot removal (clearing a hematoma).

25

30

It is envisioned that most of the above described surgical procedures will be performed in a liquid field. It is known that if sufficient pulse energies are used, vapor bubbles will be formed in

35

the liquid medium. The vapor bubbles are formed due to the high absorption of the erbium laser wavelength in water. The creation and subsequent collapse of the vapor bubble creates an acoustic shock wave which can further enhance the ablation effects of the system.

It is also possible to use the erbium laser in a dry or air field. Operating in a dry field will be particularly desirable where the tissue is fragile and destruction due to acoustic effects should be minimized. For example, if the subject erbium laser system is used to ablate tissue associated with the nervous system, it may be desirable to work in air thereby providing the most precise and accurate ablation. In this manner, the less targeted destruction associated with the acoustic effects can be avoided.

In summary, there has been disclosed a medical laser system for ablating biological material. The system includes a high repetition rate erbium laser generating a pulsed output having a wavelength of 2.9 microns. The pulsed output is generated at a rate of at least 50 hertz and preferably at least 100 hertz. The output can be used to ablate or emulsify tissue quickly with minimal thermal damage.

While the subject invention has been described with reference to the preferred embodiments, various changes and modifications could be made therein, by one skilled in the art, without varying from the scope and spirit of the subject invention as defined by the appended claims.

CLAIMS

1. A laser system for treating biological material comprising:

a resonant cavity;

5 an erbium doped solid state gain medium located within said cavity;

a flashlamp for periodically exciting said gain medium to generate output pulses;

10 power supply for energizing said flashlamp; means connected to and controlling said power supply and functioning to generate a pulsed output at a repetition rate of at least 50 hertz; and

15 means for delivering said pulsed output to said biological tissue.

2. A system as recited in claim 1 wherein each of said output pulses has an energy of at least 50 millijoules.

20 3. A system as recited in claim 1 wherein each of said output pulses has an energy of at least 100 millijoules.

4. A system as recited in claim 1 wherein the energy of each of said output pulses delivered to the tissue is at least 0.5 millijoules.

25 5. A system as recited in claim 1 wherein said resonant cavity includes a partially reflecting mirror defining an output coupler and wherein percentage transmission of the output coupler at the wavelength of the output pulses is less than eight
30 percent.

6. A system as recited in claim 5 wherein the reflectivity of the output coupler is at least two percent.

5 7. A system as recited in claim 5 wherein the reflectivity of the output coupler is four percent.

8. A system as recited in claim 1 wherein the gain medium has an optical axis and two opposed end surfaces, and wherein the end surfaces are provided with concave configurations to reduce the effects of thermal lensing in the gain medium.

10

9. A system as recited in claim 1 further including a means associated with the delivery means for aspirating the material being vaporized from the treatment site.

15 10. A system as recited in claim 1 wherein the repetition rate of the output pulses is at least 75 hertz.

11. A system as recited in claim 1 wherein the repetition rate of the output pulses is at least 100 hertz.

20

12. A system as recited in claim 1 wherein said delivery means includes an optical fiber.

13. A system as recited in claim 1 further comprising:

a second resonant cavity;

5 a second erbium doped solid state gain medium located within said second cavity;

a second flashlamp for periodically exciting said second gain medium to generate output pulses, said second flashlamp being connected to said power supply and said control means; and

10 means for combining the pulsed output from said cavities along a common optical axis and into said delivery means and wherein said control means functions to alternately energize said flashlamps so that a pulsed output is generated at twice the repetition rate of the pulsed output from each individual resonant cavity.

14. A system as recited in claim 1 further comprising:

20 a plurality of resonant cavities, with each said cavity including an erbium doped solid state gain medium located therein;

25 optical means for periodically exciting the gain media to generate output pulses, said optical means being connected to said power supply and said control means; and

30 means for combining the pulsed output from said cavities along a common optical axis and into said delivery means and wherein said control means functions to sequentially excite said gain media so that a pulsed output is produced at a repetition rate which represents the combined pulsed output from each individual resonant cavity.

35

15. A method of treating biological material comprising the steps of:

5 exciting an erbium doped gain medium to
generate a pulsed laser output having a
repetition rate of at least 50 hertz; and
delivering the pulsed output to the
biological material in a manner such that the
tissue is vaporized, ablated or incised.

10 16. A system as recited in claim 15 wherein the
energy of each of said output pulses delivered to the
tissue is at least 0.5 millijoules.

17. A method as recited in claim 15 wherein the
pulsed output is delivered to the material via an
optical fiber.

15 18. A method as recited in claim 15 further
including the step of aspirating the material which
is being treated.

19. A method as recited in claim 15 wherein the
wavelength of the pulsed laser output is 2.9 microns.

20 20. A method as recited in claim 15 wherein the
repetition rate of the output pulses is at least 75
hertz.

25 21. A method as recited in claim 15 wherein the
repetition rate of the output pulses is at least 100
hertz.

22. A method of emulsifying and removing biological tissue comprising the steps of:
exciting an erbium doped gain medium to generate a pulsed laser output having a repetition rate of at least 50 hertz;
delivering the pulsed output to the biological tissue to emulsify the tissue; and aspirating the emulsified tissue.

23. A method as recited in claim 22 wherein the repetition rate of said pulsed laser output is at least 100 hertz.

24. A method of ablating and removing biological tissue comprising the steps of:
exciting an erbium doped gain medium to generate a pulsed laser output having a repetition rate of at least 50 hertz;
delivering the pulsed output to the biological tissue to ablate the tissue; and aspirating the ablated tissue.

25. A method as recited in claim 24 wherein the repetition rate of said pulsed laser output is at least 100 hertz.

26. A method of incising and removing biological tissue comprising the steps of:
exciting an erbium doped gain medium to generate a pulsed laser output having a repetition rate of at least 50 hertz;
delivering the pulsed output to the biological tissue to incise the tissue; and aspirating the incised tissue.

27. A method as recited in claim 26 wherein the repetition rate of said pulsed laser output is at least 100 hertz.

5 28. A method of performing
photophacoemulsification comprising the steps of:
 exciting an erbium doped gain medium to
 generate a pulsed laser output having a
 repetition rate of at least 50 hertz;
10 supplying the laser output to an input end
of a delivery device;
 positioning a delivery end of the delivery
device within the vitreous of the eye to be
treated; and
15 delivering the pulsed output to the
vitreous to emulsify the tissue while
simultaneously aspirating the emulsified tissue.

29. A method as recited in claim 28 wherein the repetition rate of said pulsed laser output is at least 100 hertz.

AMENDED CLAIMS

[received by the International Bureau on 24 September 1996 (24.09.96);
original claims 1-29 replaced by amended claims 1-25 (6 pages)]

1. A laser system for treating biological material comprising:
 a resonant cavity;
 an erbium doped solid state gain medium located within said cavity;
 a flashlamp for periodically exciting said gain medium to generate output pulses;
 power supply for energizing said flashlamp;
 means connected to and controlling said power supply and functioning to generate a pulsed output at a repetition rate greater than 100 hertz; and
 means for delivering said pulsed output to said biological tissue.

2. A system as recited in claim 1 wherein each of said output pulses has an energy of at least 50 millijoules.

3. A system as recited in claim 1 wherein each of said output pulses has an energy of at least 100 millijoules.

4. A system as recited in claim 1 wherein the energy of each of said output pulses delivered to the tissue is at least 0.5 millijoules.

5. A system as recited in claim 1 wherein said resonant cavity includes a partially reflecting mirror defining an output coupler and wherein percentage transmission of the output coupler at the wavelength of the output pulses is less than eight percent.

6. A system as recited in claim 5 wherein the reflectivity of the output coupler is at least two percent.

7. A system as recited in claim 5 wherein the reflectivity of the output coupler is four percent.

8. A system as recited in claim 1 wherein the gain medium has an optical axis and two opposed end surfaces, and wherein the end surfaces are provided with concave configurations to reduce the effects of thermal lensing in the gain medium.

9. A system as recited in claim 1 further including a means associated with the delivery means for aspirating the material being vaporized from the treatment site.

10. A system as recited in claim 1 wherein said delivery means includes an optical fiber.

11. A system as recited in claim 1 further comprising:

- a second resonant cavity;
- a second erbium doped solid state gain medium located within said second cavity;
- a second flashlamp for periodically exciting said second gain medium to generate output pulses, said second flashlamp being connected to said power supply and said control means; and

means for combining the pulsed output from said cavities along a common optical axis and into said delivery means and wherein said control means functions to alternately energize said flashlamps so that a pulsed output is generated at twice the repetition rate of the pulsed output from each individual resonant cavity.

12. A system as recited in claim 1 further comprising:

- a plurality of resonant cavities, with each said cavity including an erbium doped solid state gain medium located therein;

- optical means for periodically exciting the gain media to generate output pulses, said optical means being connected to said power supply and said control means; and

means for combining the pulsed output from said cavities along a common optical axis and into said delivery means and wherein said control means functions to sequentially excite said gain media so that a pulsed output is produced at a repetition rate which represents

the combined pulsed output from each individual resonant cavity.

13. A method of treating biological material comprising the steps of:

exciting an erbium doped gain medium to generate a pulsed laser output having a repetition rate greater than 100 hertz; and delivering the pulsed output to the biological material in a manner such that the tissue is vaporized, ablated or incised.

14. A system as recited in claim 13 wherein the energy of each of said output pulses delivered to the tissue is at least 0.5 millijoules.

15. A method as recited in claim 13 wherein the pulsed output is delivered to the material via an optical fiber.

16. A method as recited in claim 13 further including the step of aspirating the material which is being treated.

17. A method as recited in claim 13 wherein the wavelength of the pulsed laser output is 2.9 microns.

18. A method of emulsifying and removing biological tissue comprising the steps of:
 exciting an erbium doped gain medium to generate a pulsed laser output having a repetition rate greater than 100 hertz;
 delivering the pulsed output to the biological tissue to emulsify the tissue; and
 aspirating the emulsified tissue.

19. A method of ablating and removing biological tissue comprising the steps of:
 exciting an erbium doped gain medium to generate a pulsed laser output having a repetition rate greater than 100 hertz;
 delivering the pulsed output to the biological tissue to ablate the tissue; and
 aspirating the ablated tissue.

20. A method of incising and removing biological tissue comprising the steps of:
 exciting an erbium doped gain medium to generate a pulsed laser output having a repetition rate greater than 100 hertz;
 delivering the pulsed output to the biological tissue to incise the tissue; and
 aspirating the incised tissue.

21. A method of performing photophacoemulsification comprising the steps of:
 exciting an erbium doped gain medium to generate a pulsed laser output having a repetition rate greater than 100 hertz;
 supplying the laser output to an input end of a delivery device;
 positioning a delivery end of the delivery device within the vitreous of the eye to be treated; and
 delivering the pulsed output to the vitreous to emulsify the tissue while simultaneously aspirating the emulsified tissue.
22. A laser system for treating biological material comprising:
 means for generating a pulsed laser output having a repetition rate of at least 100 hertz and an output wavelength of 2.9 to 2.9 microns;
 and
 means for delivering said laser output pulses to said biological tissue with an energy per pulse of at least 0.25 millijoules.
23. A system as recited in claim 22 wherein said delivery means further includes a means for aspirating the tissue.
24. A system as recited in claim 22 wherein said delivery means is defined by a flexible fiber.
25. A system as recited in claim 22 wherein said delivery means is defined by a hollow waveguide.

STATEMENT UNDER ARTICLE 19

In response to the transmittal of the Search Report, Applicant has amended the claims in the application. In particular, Applicant has limited the claims to an erbium doped laser media or their equivalent having an output with a repetition rate greater than 100 hertz.

In the Search Report, the Examiner cited a number of references related to medical devices and medical lasers using an erbium doped laser medium. WO 89 11261 describes a hand piece with multiple erbium YAG rods mounted about a single flashlamp. The specification at page 11, line 7 indicates that the flashlamp 12 produces output flashes at a rate of 10 to 100 pulses per second. Applicant has doubts that this laser would operate at this rate; however, rather than getting into a dispute over that issue, applicant has deleted any claims for a laser operating at less than 100 hertz.

The Examiner also cited EPO 626229 as being of particular relevance. However, this reference describes operation at 30 to 50 pulses per second. Applicant also notes that U.S. Patent No. 5,342,198 suggests that it would be desirable to use a laser having a repetition rate up to 10,000 pulses per second. However, there is no disclosure anywhere in this patent as to how one would manufacture such a laser and, therefore, this references is not enabling.

Applicant also notes that EP 335714 describes a laser with a pulse width of 200 microseconds and a pulse rate of 10 nanoseconds. Since repetition rates are typically described in terms of pulses per second, it may be that the author intended to describe operation at 10 hertz. At the very least, the description is ambiguous and fails to provide an enabling disclosure of a laser capable of operating at greater than 100 hertz.

It is believed that the claims remaining in the application are novel and define an inventive step.

1/5




FIG. 1




FIG. 2





FIG. 3

COMPARISON OF FILTERS AT 150 Hz 200 μ SECS FOR Er:YAG**FIG. 4**




FIG. 5




FIG. 6




FIG. 7

INTERNATIONAL SEARCH REPORT

 International Application No
 PCT/US 96/04515

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 H01S3/16 A61B17/36 H01S3/092 H01S3/102

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H01S A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO,A,89 11261 (RICHARD T. SCHNEIDER ET AL.) 30 November 1989	1,9-11, 22,23,28
Y	see page 11, line 1 - page 11, line 23	24
A	see page 12, line 2 - page 12, line 33	
	see page 16, line 4 - page 16, line 22; figures 2,3	5-7,13, 14

X	EP,A,0 626 229 (LASER MEDICAL TECHNOLOGY) 30 November 1994	1,4, 10-12, 15-17, 20,21
A	see column 1, line 10 - column 1, line 41 see column 2, line 53 - column 2, line 56 see column 3, line 40 - column 5, line 9 see column 6, line 41 - column 6, line 52 see column 7, line 14 - column 7, line 49 see column 8, line 38 - column 8, line 48; figure 1	5

	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

 X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
 Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

Z document member of the same patent family

Date of the actual completion of the international search

26 June 1996

Date of mailing of the international search report

24. 07. 96

Name and mailing address of the ISA

 European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
 Fax (+ 31-70) 340-3016

Authorized officer

Gnugesser, H

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 96/04515

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US,A,5 246 436 (T. SCOTT ROWE) 21 September 1993 see column 1, line 46 - column 2, line 15 see column 2, line 61 - column 3, line 6 see column 3, line 48 - column 4, line 39; figures 1,2 ---	24
X	US,A,5 401 171 (AHID F. PAGHDIWALA) 28 March 1995	1-4,15, 16
A	see column 2, line 24 - column 2, line 65 see column 3, line 3 - column 3, line 11 see column 3, line 48 - column 4, line 6 see column 4, line 65 - column 5, line 54 see column 6, line 50 - column 7, line 3; figures 1-3 ---	5-7,22, 24,26,28
X	EP,A,0 575 274 (LASER MEDICAL TECHNOLOGY) 22 December 1993	1,15
A	see column 3, line 52 - column 4, line 19 see column 4, line 55 - column 5, line 54 see column 7, line 6 - column 7, line 21 see column 9, line 36 - column 9, line 37; figures 1-3 ---	13,14, 22,24, 26,28
A	US,A,5 342 198 (ARTHUR VASSILIADIS ET AL.) 30 August 1994 see column 2, line 3 - column 2, line 28 see column 4, line 7 - column 4, line 30; figure 1 ---	1,22-29
A	PATENT ABSTRACTS OF JAPAN vol. 16, no. 14 (E-1154), 17 October 1991 & JP,A,03 233986 (SONY CORPORATION), 17 October 1991, see abstract ---	1,8
A	US,A,5 375 132 (KEVIN P. CONNORS ET AL.) 20 December 1994 whole document; cited in the application ---	1,13,14
A	US,A,4 988 163 (MARTIN G. COHEN ET AL.) 29 January 1991 see column 1, line 38 - column 1, line 43 see column 2, line 10 see column 3, line 8 - column 3, line 50 see column 4, line 20 - column 4, line 32; figure 2 ---	15,22, 24,26,28

	-/--	

3.

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 96/04515

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP,A,0 335 714 (SITE MICROSURGICAL SYSTEMS, INC) 4 October 1989 see column 2, line 38 - column 3, line 6 see column 3, line 41 - column 4, line 32 see column 5, line 28 - column 6, line 4; claims 9,10; figure 1 ---	15,22, 24,28
P,X	US,A,5 422 899 (ROBERT J. FREIBERG ET AL.) 6 June 1995 see column 1, line 37 - column 1, line 66 see column 3, line 33 - column 3, line 48 see column 4, line 15 - column 4, line 58 see column 5, line 35 - column 5, line 56 see column 8, line 28 - column 8, line 56; figures 1,2,9; table I -----	15,16,19

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 96/04515

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A-8911261	30-11-89	US-A- 5074861	24-12-91
EP-A-626229	30-11-94	JP-A- 7136185	30-05-95
US-A-5246436	21-09-93	NONE	
US-A-5401171	28-03-95	NONE	
EP-A-575274	22-12-93	US-A- 5290274	01-03-94
US-A-5342198	30-08-94	US-A- 5257935	02-11-93
		AU-B- 619000	16-01-92
		AU-B- 3281789	05-10-89
		CA-A- 1319960	06-07-93
		DE-T- 68906734	13-01-94
		EP-A, B 0357760	14-03-90
		JP-T- 2504478	20-12-90
		WO-A- 8908432	21-09-89
US-A-5375132	20-12-94	EP-A- 0697143	21-02-96
		WO-A- 9426010	10-11-94
US-A-4988163	29-01-91	NONE	
EP-A-335714	04-10-89	AU-B- 3221589	05-10-89
		GR-A- 89100203	31-07-91
		JP-A- 1299546	04-12-89
US-A-5422899	06-06-95	AU-B- 1796495	16-11-95
		CA-A- 2148395	11-11-95
		EP-A- 0682389	15-11-95